Willow Play & Park Structures 10-136029 PLAY SYSTEMS 37'-2" Minimum Area Required: 43'-9" x 37'-2" 69266 69266 69266 69499 This play equipment is recommended for children ages: 5-12 CASCADE DOUBLE ENTRANCE 69262 SLIDE SUPPORT 69268 69266 69266 69266 69499 Scale: 3/16" = 1'-0" This drawing can be scaled only when in an 11" x 17" format HALF HEX SLAT ROOF 69529 TREEFORT
SPY PANEL
69531
BENCH SEAT
(BELOW)
63994 TREEFORT CLUBHOUSE CLIMBER CMBER 69528 43'-9" Quote Number: 10-136029 SUPPORT 69268 Date: 7/12/2022 Drawn By: ထ္ COIL CLIMBER 63728 ROPE LADDER 69526 ထ္ TRIANGLE
TRANSFER POINT
W\BARRIER
69149
RETURN STEP
62345 0 BEAN STALK CLIMBER 69381 LEG LIFT 62243 544 Chestnut Street Chattanooga, TN 37402 800-727-1907 / www.playandpark.com structures: play⊗park HAND PEDALER 62412 4,8, SQUARE SLAT ROOF 69527 CURVED VELOCITY
SLIDE
69329 ZIP STEP CLIMBER 69253 69147 DECK TO DECK STAIRS (3'-4" RISE) 1005 SQ FT MINIMUM SURFACING F 口 Elevated Play Components Elevated Components Accessible by Transfer Elevated Play Components Accessible by Ramp Total Different Types of Ground Level Components Accessible Ground Level Components Shown Play Components 0 8 ယ ယ ထ Req. 0 Req. 4 Req. Req. Critical Fall Height 8'-0" User Capacity 40-50 S O O O O

It is the manufacturer's opinion that the structure shown herein complies with current ada standards conceming accessibility if used with proper accessible surfacing and together with other necessary ground level play equipment.

IMPORTANT: Never install play equipment over hard, unresilient surfaces such as asphalt, concrete, or compacted earth. It is the owner's responsibility to ensure the "minimum area required" contains an appropriate amount of resilient material to cushion accidental falls.